JH21A 开式固定台压力机（喉口加强型）

C-frame Fixed Bolster Press (Laryngeal enhancement)

秀外慧中，智者风范

持重端庄的外形结构，细腻考究的油漆工艺，颇具匠心的制造技术，业界顶级的精品配置，久经考验的内在品质，精益求精的开放心态，尽显沃得精机JH21系列压力机的智者风范。

有智者，成大志。

标准配置

- 沃得高性能湿式离合器
- 液压过载保护装置
- 电动黄油润滑装置
- 手动稀油润滑装置
- 滑块及上模平衡装置
- 误送检知接口
- 触摸屏
- 电子式曲轴角度指示器
- 凸轮控制器
- 电动滑块调整装置
- 可编程控制器
- 空气源快速接头
- 减震垫
- 工作灯
- 空气吹料
- 二度落
- 预调计数器（触摸屏显示）

Standard Equipments

- Wet clutch(World)
- Hydraulic overload protecting pump
- Auto lubrication system
- Manual lubrication system
- Balance cylinders for slide and upper die
- Joint for miss-feeding
- Touch screen
- Electronic crankshaft angle indicator
- Cam controller
- Die height adjusted motor
- PLC : Programmable logical controller
- Air source quick connector
- Shock Absorption Pads
- Working lamp
- Air blowing
- Second degree drop
- Preset counter(Touch screen display)

技术参数 Specifications		JH21A–160	JH21A–200	JH21A–250	JH21A–315	JH21A–400
公称力 Nominal Pressure		1600	2000	2500	3150	4000
公称力行程 Nominal Stroke		6	6	6.5	7	8
滑块行程 Slide Stroke		200	200	220	220	250
行程次数 Slide Strokes Per Minute	固定 Fixed	45	45	33	33	30
	可变 Variable	30–55	30–55	25–40	25–40	20–35
最大装模高度 Max Die Set Height		400	450	500	500	550
装模高度调节量 Die Height Adjustment		100	110	120	120	120
滑块中心至机身距离 Throat Depth		400	430	450	450	450
立柱距离 Distance Between Uprights		676	910	980	980	1050
滑块底面尺寸 Slide Bottom Size	左右 L x R	700	880	900	900	1020
	前后 F x B	580	650	700	700	750
模柄孔尺寸 Shank Hole Size	直径 Dia	70	70	70	70	70
	深度 Depth	100	100	100	100	100
工作台板尺寸 Bolster Size	右 L x R	1175	1390	1500	1540	1700
	前后 F x B	760	840	880	880	880
落料孔直径 Blanking Hole Diameter		220	240	240	240	240
工作台板厚度 Bolster Thickness		165	180	190	190	210
工作台离地面距离 Bolster Surface Height		900	1000	1000	1000	1100
外形尺寸 Overall Dimensions	前后 F x B	2305	2600	2660	2720	2850
	右 L x R	1480	1620	1720	1760	1840
	高 H	3210	3800	3850	3850	4140
地脚螺栓距离 Distance Between Foundation Bolts	前后 F x B	1665	2020	2230	2200	2385
	左右 L x R	1140	1360	1460	1500	1570
电动机 Motor	功率 Power	15	18.5	22	30	37
压机气压 Press Pressure		0.5				

性能特点

- 喉口刚性增强，适应于中厚板及高强度板材落料

Features

- Throat rigidity is enhanced, which is suitable for blanking of medium and heavy plates and high-strength plates

选用配置

- 干式离合制动器
- 气垫装置
- 光电保护装置
- 快速换模装置
- 脚踏开关
- 输出轴
- 变频调速
- 滑块上部脱料装置

（用户选用，应在合同中注明）

Optional Equipments

- Dry clutch
- Air cushion apparatus
- Light curtain Protection
- Die quick change device
- Foot pedal
- Output shaft
- Frequency control
- Top stripping device for slider

(User selection should be specified in the contract)

